



Ceiling Modern



Description

The LITELUME™ Ceiling Modern (LL-CM) luminaire incorporates special binned high CRI LED's placed for even distribution of lighting in this modern soft design. Features a die-formed cold rolled steel housing in satin nickel or oil rubbed bronze with a high transmission acrylic lens for a soft appearance. Offering 2 different sizes and wattages. Available in 3000k, high power factor and low THD.

Applications: commercial, residential, hospitality and entertainment.

Fixture Information

Size:	17W/23W
Housing:	Die-formed cold rolled steel
Finish:	Protective powder coat
Color:	Standard: Satin Nickel (SN) Standard: Oil Rubbed Bronze (ORB)
Mounting:	Standard: Ceiling Mount
Lens:	High Transmission Acrylic
CRI:	80
Power Factor:	.90
Voltage:	Standard: 120-277V
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

1100 to 1500 lm

Lumens Per Watt (typical):

65 lm/W

CCT:

3000K

Ratings & Certificates


ETL/cETL Listed
Damp Location Listed





Dimension

Item	Diameter (a)	Height (b)
17W	14.0"	2.5"
23W	16.0"	2.5"





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-CM-17-30-UNV-SN	17	1100	3000	120-277	Satin Nickel
LL-CM-17-30-UNV-ORB	17	1100	3000	120-277	Oil Rubbed Bronze
LL-CM-23-30-UNV-SN	23	1500	3000	120-277	Satin Nickel
LL-CM-23-30-UNV-ORB	23	1500	3000	120-277	Oil Rubbed Bronze