



Description

The LITELUME™ Slimpack (LL-SP) features a die-formed cold rolled steel housing with a UV-resistant polycarbonate optical lens for long-lasting durability. The compact size allows for multi use in many different applications replacing up to 100w.

Applications: Security, Pathway, Perimeter, Hallway and Walkway lighting.

Fixture Information

Size:	15W
Housing:	Die-formed Cold Rolled Steel
Finish:	Protective powdercoat
Color:	Standard: Black (BK)
Mounting:	Standard: Wall Mount
Lens:	Polycarbonate
CRI:	80
Power Factor:	.90
Voltage:	Standard: 120-277V
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

550 to 660 lm

Lumens Per Watt (typical):

36 to 40 lm/W

CCT:

3000K

4000K

Lifespan:

50,000 running hours

Ratings & Certificates



UL Wet Location Listed





Dimension

Item	Width	Length	Height
15W	4.9"	4.5"	9.9"





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage
LL-SP-15-40-UNV-BK	15	600	4000	120-277
LL-SP-15-30-UNV-BK	15	550	3000	120-277

* Please contact LITELUME for all Custom Option Requests