



WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

Product Information

The LITELUME™ Wallpack Medium (LL-WPM) features die-cast aluminum housing with a UV resistant polycarbonate optical lens for long-lasting durability.



Applications: Hallway, Perimeter lighting and Walkway lighting.

Ratings & Certifications

- ✦ UL Wet location listed
- ✦ DLC qualified

Performance Summary

- ✦ Lumen Output: 3,467-7,231lm
- ✦ Lumen Per Watt (typical): 110 - 125m/W
- ✦ CCT: 4000K, 5000K
- ✦ Lifespan: Features Philips Lumileds with up to 100,000 running hours.



Fixture Information

- ✦ Size: 28W/42W/65W
- ✦ Housing: Die-cast aluminum housing
- ✦ Finish: Protective powdercoat
- ✦ Colors: Standard: Bronze
Custom Options: Black (BK), White (WH), Gray (GY)
- ✦ Mounting: Standard: Wall Mount
- ✦ Lens: Polycarbonate
- ✦ Surge Protector: Standard: 10 kVA
- ✦ Voltage: Standard: 120-277V
- ✦ Sensors: Standard: No sensor
Custom Options: Button Photocell (120-277V)
- ✦ Warranty: 10-Year Limited Warranty

FIXTURE ORDERING INFORMATION

Item #	Part #	Wattage	Lumens	Kelvin	Voltage	Custom Options Available*
2010	LL-WPM-28-50-UNV-BZ	28.49	3,564	5000	120-277V	Yes
2011	LL-WPM-28-40-UNV-BZ	28.38	3,467	4000	120-277V	Yes
2020	LL-WPM-42-50-UNV-BZ	42.67	4,801	4000	120-277V	Yes
2021	LL-WPM-42-40-UNV-BZ	42.69	4,701	5000	120-277V	Yes
2030	LL-WPM-65-50-UNV-BZ	63.12	7,231	4000	120-277V	Yes
2031	LL-WPM-65-40-UNV-BZ	64.63	7,212	5000	120-277V	Yes

*Please contact LITELUME for all Custom Option Requests





WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

Mounting

✧ Standard wall mount available

Dimensions And Weights

FIXTURE DIMENSIONS AND WEIGHTS

Item #	Length	Width	Height	Weight
Wallpack Medium	14.212"	7.40"	9.252"	15lb

Sensor and Photocell Options

SENSOR AND PHOTOCELL ORDERING INFORMATION

Item #	Part #	Description
23	PC	Button Photocell 120-277V

*Please contact LITELUME for all Custom Option Requests





WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

LL-WPM-28-50-UNV-BZ

A Program of the U.S. DOE

LITE LUME

Light Output (Lumens)	3550
Watts	28.49
Lumens per Watt (Efficacy)	124.61

Color Accuracy Color Rendering Index (CRI)	70
--	-----------

Light Color
Correlated Color Temperature (CCT) **5000 (Daylight)**

2700K
3000K
4500K
6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: SH7Y-KLVJFL (10/25/2017)
Model Number: LL-WPM-28-50-UNV-BZ
Type: Luminaire - Area/Roadway

LL-WPM-28-40-UNV-BZ

A Program of the U.S. DOE

LITE LUME

Light Output (Lumens)	3450
Watts	28.38
Lumens per Watt (Efficacy)	121.56

Color Accuracy Color Rendering Index (CRI)	70
--	-----------

Light Color
Correlated Color Temperature (CCT) **4000 (Bright White)**

2700K
3000K
4500K
6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: SH7Y-57YZOQ (10/25/2017)
Model Number: LL-WPM-28-40-UNV-BZ
Type: Luminaire - Area/Roadway





WALLPACK MEDIUM

LL-WPM-28-40-UNV-BZ


Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:





WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

LL-WPM-42-50-UNV-BZ

LL-WPM-42-40-UNV-BZ

LED LITELUME

lighting facts®

A Program of the U.S. DOE

Light Output (Lumens)	4801
Watts	42.67
Lumens per Watt (Efficacy)	112.51

Color Accuracy	75
Color Rendering Index (CRI)	

Light Color
Correlated Color Temperature (CCT) **5200 (Daylight)**

2700K 3000K 4500K 6500K

Warm White Bright White Daylight

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the *Label Reference Guide*.

Registration Number: SH7Y-1DU6NF (12/6/2017)
 Model Number: LL-WPM-42-50-UNV-BZ
 Type: Luminaire - Area/Roadway

LED LITELUME

lighting facts®

A Program of the U.S. DOE

Light Output (Lumens)	4702
Watts	42.69
Lumens per Watt (Efficacy)	110.14

Color Accuracy	76
Color Rendering Index (CRI)	

Light Color
Correlated Color Temperature (CCT) **4021 (Bright White)**

2700K 3000K 4500K 6500K

Warm White Bright White Daylight

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the *Label Reference Guide*.

Registration Number: SH7Y-WI711B (12/6/2017)
 Model Number: LL-WPM-42-40-UNV-BZ
 Type: Luminaire - Area/Roadway






WALLPACK MEDIUM

Project Name:
Catalog #:
Job Type:
Prepared by:
Notes:

LL-WPM-42-40-UNV-BZ



LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to update product specifications without notice. Contact LITELUME™ for the most up-to-date data. ©2017 Rev Date: 8.1.17 v 1.4





WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

LL-WPM-65-50-UNV-BZ

LL-WPM-65-40-UNV-BZ

LITELUME

A Program of the U.S. DOE

Light Output (Lumens)	7231
Watts	63.12
Lumens per Watt (Efficacy)	114.56

Color Accuracy Color Rendering Index (CRI)	75
--	-----------

Light Color
Correlated Color Temperature (CCT)

5112 (Daylight)

2700K
3000K
4500K
6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the *Label Reference Guide*.

Registration Number: SH7Y-3AE4Y4 (11/22/2017)
Model Number: LL-WPM-65-50-UNV-BZ
Type: Luminaire - Area/Roadway

LITELUME

A Program of the U.S. DOE

Light Output (Lumens)	7213
Watts	64.63
Lumens per Watt (Efficacy)	111.6

Color Accuracy Color Rendering Index (CRI)	73
--	-----------

Light Color
Correlated Color Temperature (CCT)

4041 (Bright White)

2700K
3000K
4500K
6500K

All results are according to IESNA LM-79-2008: *Approved Method for the Electrical and Photometric Testing of Solid-State Lighting*. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the *Label Reference Guide*.

Registration Number: SH7Y-C67UA3 (11/22/2017)
Model Number: LL-WPM-65-40-UNV-BZ
Type: Luminaire - Area/Roadway





WALLPACK MEDIUM

Project Name:

Catalog #:

Job Type:

Prepared by:

Notes:

LL-WPM-65-40-UNV-BZ

