



Wallpack Medium Full Cutoff



Description

The LITELUME™ Wallpack Medium (LL-WPMFC) is a mid-sized, full cutoff LED fixture featuring die-cast aluminum housing and a superior dual coat finish.

Applications: Entryways, Tunnels, and Walkways.

Fixture Information

Size:	28W/42W
Housing:	Die-cast Aluminum Housing
Finish:	Protective powdercoat
Color:	Standard: Bronze Custom Options: Black (BK) White (WH) Grey (GY)
Mounting:	Standard: Wall Mount
Lens:	Polycarbonate
Surge Protector:	Optional: 10 kVA
Voltage:	Standard: 120-277V
Sensor:	Standard: No sensor Custom: Button Photocell (120-277V)
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

3,601 to 5,038 lm

Lumens Per Watt (typical):

114-121 lm/W

CCT:

4000K
5000K

Distribution:

Type III

Lifespan:

Features Philip Lumileds with up to 100,000 running hours

Ratings & Certificates

UL Listed For Wet Location
DLC Qualified







Dimension

Item	Width	Length	Height	Weight
Wallpack Medium Full Cutoff	8.78"	14.21"	9.25"	15.50 lb
Wallpack Medium Full Cutoff w/Sensor	8.78"	14.21"	10.00"	15.50 lb

Without Sensor




With Sensor



Photometrics

Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 102.7°



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Item #	Part #	Wattage	Lumens	Kelvin	Voltage	Custom Option Available*	
2210	LL-WPMFC-28-50-UNV-BZ	28	3670	5000	120-277	Yes	
2211	LL-WPMFC-28-40-UNV-BZ	28	3601	4000	120-277	Yes	
2212	LL-WPMFC-42-50-UNV-BZ	42	5038	5000	120-277	Yes	
2213	LL-WPMFC-42-40-UNV-BZ	42	4992	4000	120-277	Yes	

* Please contact LITELUME for all Custom Option Requests

Accessories Ordering Information

Item #	Part #	Wattage
23	PC	Button Photocell, 120-277V
40	MS40	Bi-Level Microwave Motion Sensor 40
41	RC41	Remote Control 41
301	MSFSP211	Wattstopper Fsp-211 Bi-Level Pir Motion Sensor
302	FSPL2	Lens Module For Fsp-211 48" Diameter From 8' Mounting Height
303	FSPL3	Lens Module For Fsp-211 40" Diameter From 20' Mounting Height
304	FSPL7	Lens Module For Fsp-211 100" Diameter From 40' Mounting Height
305	FSIR100	Wattstopper Fsir-100 Wireless Configuration Tool for Fsp-211
	SUB "UNV" WITH "480"	480 Volt
34	EM8	Emergency Battery Back Up 8W

* Please contact LITELUME for all Custom Option Requests

Buy American Act Compliant Ordering Information

Item #	Part #	Description
209	BAA-WPMFC	Buy American Act Compliant for Wallpack Medium Full Cutoff

* Please contact LITELUME for all Custom Option Requests