Vanity Modern Open

Description

The LITELUME™ Vanity Modern Open (LL–VMO) features a die-formed cold rolled steel housing in satin nickel or oil rubbed bronze with a high transmission acrylic shade for an elegant soft appearance.

Applications: Hallways, Vanity lighting

Fixture Information

Size:	15W/22W/32W
Housing:	Die-formed cold rolled steel
Finish:	Protective powdercoat
Color:	Standard: Satin Nickel (SN) Optional: Oil Rubbed Bronze (ORB)
Mounting:	Standard: Wall Mount
Lens:	High transmission acrylic
CRI:	80
Power Factor:	.98
Dimming:	None
THD:	<10%
Voltage:	Standard: 120-277V
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

1100 to 3000 lm

Lumens Per Watt (typical):

100 lm/W

CCT:

3000K
3500K
4000K

Lifespan:

60,000 running hours

Ratings & Certificates

ETL/cETL Listed

Intertek

LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to update product specifications without notice. Contact LITELUME™ for the most up-to-date data.

Dimension

Item	Depth	Width	Height
15W	3.7″	24″	4.3″
22W	3.7″	36″	4.3″
32W	3.7″	48″	4.3″



LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to update product specifications without notice. Contact LITELUME™ for the most up-to-date data.

Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage
LL-VMO-15-MCT-UNV-SN	15	1100	3000K/3500K/4000K	120-277V
LL-VMO-15-MCT-UNV-ORB	15	1100	3000K/3500K/4000K	120-277V
LL-VMO-22-MCT-UNV-SN	22	1900	3000K/3500K/4000K	120-277V
LL-VMO-22-MCT-UNV-ORB	22	1900	3000K/3500K/4000K	120-277V
LL-VMO-32-MCT-UNV-SN	32	3000	3000K/3500K/4000K	120-277V
LL-VMO-32-MCT-UNV-ORB	32	3000	3000K/3500K/4000K	120-277V

* Please contact LITELUME for all Custom Option Requests

LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to update product specifications without notice. Contact LITELUME™ for the most up-to-date data.