



# LL-BH1

## Bulkhead 1

The LITELUME™ Bulkhead 1 (LL-BH1) is designed to replace HID lighting systems up to 100W MH or HPS. Featuring a robust housing and lens for more demanding situations. Recommended mounting heights are 8 to 14 feet.



PERFORMANCE DATA	
Lumen Output	1100 lm
Lumens Per Watt (typical)	92 lm/W
CCT	4000K
Lifespan	70,000 hrs

RATINGS & CERTIFICATES
ETL, UL Listed • Wet Location • IP65

APPLICATIONS
Apartments • Offices • Public Buildings Condominiums • Schools • Malls General Hospitality

FIXTURE INFORMATION				
Size	Housing / Lens	Mounting	Color	Dimensions
12W	Heavy Duty Injection Molded Polycarbonate	Wall, Ceiling, Surface	White	4.3 x 5 x 9.2 in. (H x L x W)
Voltage	Power Factor	THD	CRI	Warranty
120 - 277V UNV	.90	<20%	80	10 Year Limited



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

**ORDERING GUIDE**

Brand	Fixture Type	Lumen Package	Voltage	CCT	Finish	Accessories
LL LITELUME	BH1 Bulkhead 1	1L 1100 Lumens	UNV 120-277V	40 4000K	WH White	PC Photocell

**FIXTURE ORDERING INFORMATION**

Part #	Watts	Lumens	Kelvin	Voltage
LL-BH1-1L-UNV-40-WH	12	1100	4000	120-277

**ACCESSORIES ORDERING INFORMATION**

Part #	Description
PC	Photocell