



# Amberlume Series Wall Pack Medium Full Cutoff



## Description

The Litelume Amberlume Series Wall Pack Medium Full Cutoff (LL-ALWPMFC) luminaire is available in an IES Type V distribution and designed to replace HID lighting systems 175w to 250w MH or HPS for wildlife or security applications requiring monochromatic AMBER light. LEDs operate between 585 and 595 nm, greater than 560nm required for wildlife protection. Typical wall mounted lighting applications include retail centers, industrial parks, schools and universities, office buildings and medical facilities. Mounting heights of 12 to 18 feet can be used based on light level and uniformity requirements.

## Fixture Information

Size:	36W
Housing:	Die Cast Hinged and Gasketed Aluminum Front Frame and Housing with ½" Coin Plugs
Finish:	Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating
Lens:	Standard: Tempered Clear Flat Glass Lens
Temperature:	-40°C to +40°C
Voltage:	Standard: 120-277V
Power Factor:	>.90
Surge Protector:	6 kVA
Warranty:	10-Year Limited Warranty

## Performance Data

### Lumen Output:

1518 lm

### Lumens Per Watt (typical):

40 lm/W

### CCT:

Amber

### Lifespan:

213,000 hrs @ 25°C (L70)

### Ratings & Certificates


CSA Listed for Wet Locations  
IP65 rated







### Dimension

Item	Height	Width	Depth
36W	9.125"	14.25"	11.375"



### Photometric

LL-ALWPMFC-36-AMB-UNV-BZ





<b>Project Name</b>	
<b>Catalog #</b>	
<b>Job Type</b>	
<b>Prepared By</b>	
<b>Notes</b>	

## Fixture Ordering Information

Part #	Wattage	Lumens	CCT	Voltage	Color
LL-ALWPMFC-36-AMB-UNV-BZ	36	1518	Amber	120-277V	Bronze

## Accessories Ordering Information

Part #	Description
SF	Single Fuse <i>*120-277V Only*</i>
DF	Double Fuse <i>*120-277V Only*</i>
SP	Surge Protection
PC3	Photocell, 120-277V
BU	Battery Backup, 90 Minutes <i>*120-277V Only*</i>
SUB "UNV" WITH "480"	480 Volt

\* Please contact LITELUME for all Custom Option Requests