

Sconce Block Mood Uplight/Downlight







Description

The LITELUME™ Sconce Block Mood Uplight/Downlight (LL–SBM-UD/LL-SBM-D) luminaire incorporates a simple fresh small form factor design. Features a die-formed cold rolled steel housing in black, with availability to special order in bronze or custom colors with a crystal glass lens. Offering a standard 8w & 10w model in 3000k or 4000k(special order), high power factor and low THD.

Applications: commercial, residential, hospitality and entertainment

Fixture Information

Size: 8W/10W

Housing: Die-formed cold rolled steel Protective

Finish: powder coat

Color: Standard: Black (BK)

Optional Special Order: Bronze (BZ)
Optional Special Order: Custom (CUS)

Mounting: Standard: Wall Mount
Lens: High Transmission Glass

CRI: 80

THD: <20%

Power Factor: .90

Voltage: Standard: 120-277V
Warranty: 10-Year Limited Warranty

Performance Data

Lumen Output:

500-650 lm

Lumens Per Watt (typical):

(typical): 65 lm/W

CCT:

3000K

4000K (SPECIAL ORDER)

Ratings & Certificates

ETL/cETL Listed
Wet Location Listed ADA
Compliant









Dimension

Item	Width	Depth	Height
8W/10W	5.0"	3.9"	5.0"







Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SBM-UD-10-30-UNV-BK	10	650	3000	120-277	Black
LL-SBM-UD-10-30-UNV-BZ	10	650	3000	120-277	Bronze
LL-SBM-UD-10-30-UNV-CUS	10	650	3000	120-277	Custom
LL-SBM-D-8-30-UNV-BK	8	500	3000	120-277	Black
LL-SBM-D-8-30-UNV-BZ	8	500	3000	120-277	Bronze
LL-SBM-D-8-30-UNV-CUS	8	500	3000	120-277	Custom

^{*} Please contact LITELUME for all Custom Option Requests