



# LED High Output Industrial Emergency Unit

## LL-LEDXR

LED High Output Industrial Remote Capable Thermoplastic Emergency Unit



### PRODUCT INFORMATION

Illumination	Electrical
<ul style="list-style-type: none"> <li>Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 6-ft path of egress at 15-ft mounting height.</li> <li>6.0 watt (12 LEDs x 0.50 watt) per head.</li> <li>Adjustable glare-free PAR-Type lamp heads with all-inclusive lamp, reflector and lens assembly</li> </ul>	<ul style="list-style-type: none"> <li>Dual 120/277 voltage.</li> <li>Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.</li> <li>LVD (low voltage disconnect) prevents battery from deep discharge.</li> <li>6V/12V maintenance-free, rechargeable sealed lead acid battery.</li> <li>Offers 38.0W and 88.0W of remote capacity (6V/12V DC output) standard on the 50W, and 100W models.</li> <li>Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.</li> <li>Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.</li> </ul>
Housing	Dimensions
<ul style="list-style-type: none"> <li>Injection-molded, engineering grade, 5VA flame retardant, high-impact thermoplastic construction.</li> </ul>	
Mounting	Warranty
<ul style="list-style-type: none"> <li>Knockouts on the back for wall mount.</li> <li>Side and top knockouts for conduit feed applications.</li> </ul>	<ul style="list-style-type: none"> <li>Five year warranty on all electronics and housing. Battery pro rated for two years.</li> <li>Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.</li> <li>UL Listed for damp locations (20°C – 40°C).</li> </ul>



# LED High Output Industrial Emergency Unit

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

## ORDERING GUIDE

Model	Voltage	Capacity	Housing Color
LL-LEDXR	6 6V 12 12V	5 50W 10 10W	WH White BK Black

## ELECTRICAL INFORMATION

Model	Input Watts (W)		Input Amps (A)	
	120V	277V	120V	277V
LL-LEDXR65	16.0	16.0	0.15	0.06
LL-LEDXR610	30.0	30.0	0.28	0.12
LL-LEDXR125	16.0	16.0	0.15	0.06
LL-LEDXR1210	30.0	30.0	0.28	0.12

## REMOTE LAMP COMPATIBILITY

Model	Battery	Remote Capacity	Compatible Remote Head Family			
			LL-HPRL	LL-RHLED-MV	LL-RH16LED	LL-SRHLED
LL-LEDXR65	6V	38W	X	X	X	X
LL-LEDXR610	6V	38W	X	X	X	X
LL-LEDXR125	12V	88W	X	X	X	
LL-LEDXR1210	12V	88W	X	X	X	