



LL-BH3

Bulkhead 3

The LITELUME™ Bulkhead 3 (LL-BH3) is designed to replace HID lighting systems up to 100W MH or HPS. Featuring a robust housing and lens for more demanding situations. Recommended mounting heights are 8 to 14 feet.



PERFORMANCE DATA

Lumen Output	1200 lm
Lumens Per Watt (typical)	75 lm/W
CCT	4000K
Lifespan	70,000 hrs

RATINGS & CERTIFICATES

ETL, UL Listed • Wet Location • IP65

APPLICATIONS

Apartments • Offices • Public Buildings
Condominiums • Schools • Malls
General Hospitality

FIXTURE INFORMATION

Size	Housing / Lens	Mounting	Color	Dimensions
16W	Heavy Duty Injection Molded Polycarbonate	Wall, Ceiling, Surface	White	3.7 × 10 × 10 in. (H × L × W)
Voltage	Power Factor	THD	CRI	Warranty
120 - 277V UNV	.90	<20%	80	10 Year Limited



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	Voltage	CCT	Finish	Accessories
LL LITELUME	BH3 Bulkhead 3	1L 1200 Lumens	UNV 120-277V	40 4000K	WH White	PC Photocell

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-BH3-1L-UNV-40-WH	16	1200	4000	120-277

ACCESSORIES ORDERING INFORMATION

Part #	Description
PC	Photocell