



LL-CAL-16

Custom Address Light Style 16

The LITELUME™ Custom Address Light Style 16 (LL-CAL-16) is a high performance LED solution with a small compact design. Each luminaire is customizable to select color finish and desired room number for hotels, apartments, condominiums, homes and offices.



Intertek

PERFORMANCE DATA

Lumen Output	760 lm	Ratings & Certificates <ul style="list-style-type: none"> • ETL/cETL Listed • Damp Location • ADA Compliant
Lumens Per Watt (typical)	51 lm/W	
CCT	3000K 4000K	
Lifespan	50,000 hrs	

APPLICATIONS

Hotels • Apartments • Condominiums
Townhomes • General Homes

Hospitality, Multi-Family & Residential Applications

FIXTURE INFORMATION

Size	Housing	Finish	Lens	Mounting	Lettering	Color
15W	Die-formed cold-rolled steel	Protective powder coat	Acrylic	Standard: Wall Mount	Standard: Silk Screen Optional: Braille	<ul style="list-style-type: none"> • Satin Nickel (SN) • Oil rubbed bronze (ORB) • Black (BK) • White (WH) • Gray (GY) • Custom (CUS)
Voltage	Dimming	Power Factor	CRI	Warranty	Dimensions	
Standard: 120-277V	No	.90	80	10 Year Limited	7.3" x 12.0" x 3.9"	



Custom Address Light Style 16

PROJECT NAME	
CATALOG #	
ROOM # SEQUENCE	
EXCLUDED ROOM #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Model	Number Style	Lumen Package
LL LITELUME	CAL Custom Address Light	16 Style 16	SS Silk Screen	1L 760 Lumens
Voltage	CCT	Finish		Accessories
UNV 120-277V	30 3000K 40 4000K	SN Satin Nickel ORB Oil Rubbed Bronze BK Black	WH White GY Gray CUS Custom	CRI90 90CRI B Braille

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-CAL-16-SS-1L-UNV-30-SN	15	760	3000	120-277V
LL-CAL-16-SS-1L-UNV-40-SN	15	760	4000	120-277V
LL-CAL-16-SS-1L-UNV-30-ORB	15	760	3000	120-277V
LL-CAL-16-SS-1L-UNV-40-ORB	15	760	4000	120-277V
LL-CAL-16-SS-1L-UNV-30-BK	15	760	3000	120-277V



Custom Address Light Style 16

LL-CAL-16-SS-1L-UNV-40-BK	15	760	4000	120-277V
LL-CAL-16-SS-1L-UNV-30-WH	15	760	3000	120-277V
LL-CAL-16-SS-1L-UNV-40-WH	15	760	4000	120-277V
LL-CAL-16-SS-1L-UNV-30-GY	15	760	3000	120-277V
LL-CAL-15-SS-1L-UNV-40-GY	15	760	4000	120-277V
LL-CAL-16-SS-1L-UNV-30-CUS	15	760	3000	120-277V
LL-CAL-16-SS-1L-UNV-40-CUS	15	760	4000	120-277V

ACCESSORIES ORDERING INFORMATION

Part #	Description
CRI90	90 CRI
B	Braille