



Bulkhead Round Open Frame Econolume Series



LL-BROFECO

Bulkhead Round Open Frame Econolume Series

The LITELUME™ Bulkhead Round Open Frame Econolume Series (LL-BROFECO) is designed to replace HID lighting systems up to 175W MH or HPS. The open door frame allows for maximum light output. Recommended mounting heights are 8 to 16 feet.



PERFORMANCE DATA

Lumen Output	1700 lm
Lumens Per Watt (typical)	74 lm/W
CCT	3000K 4000K
Lifespan	70,000 hrs

RATINGS & CERTIFICATES


ETL, UL Listed • Wet Location • IP65

APPLICATIONS

Apartments • Offices • Public Buildings
Condominiums • Schools • Malls
General Hospitality

FIXTURE INFORMATION

Size	Housing			Finish	Lens	Mounting	Color
23W	Die-Cast Aluminum with Vandal Resistant Screws			Powder Coat	Opal Polycarbonate Vandal Resistant	Wall, Ceiling, Surface	Black
Voltage	PF	THD	CRI	Dimensions (H × L × W)			Warranty
120 - 277V UNV	.90	<20%	80	3.8 × 12.8 × 12.8 in.			10 Year Limited





Bulkhead Round Open Frame Econolume Series

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	Voltage	CCT	Finish	Accessories
LL LITELUME	BROFECO Bulkhead Round Open Frame Econolume Series	2L 1700 Lumens	UNV 120-277V	30 3000K 40 4000K	BK Black	PC Photocell

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-BROFECO-2L-UNV-30-BK	23	1700	3000	120-277
LL-BROFECO-2L-UNV-40-BK	23	1700	4000	120-277

ACCESSORIES ORDERING INFORMATION

Part #	Description
PC	Photocell