




# LED Linear Wall Wash



## Description

The LITELUME™ LED Linear Wall Wash (LL-FL56) is used for landscape lighting, building facade, billboards, bridges and custom designs. The fixture provides single white, RGB and RGBW, as well as DALI dimming and DMX control functions to ensure normal use in various situations. Multiple beam angles, wattages and mounting options available.

## Fixture Information

Size:	18W/36W
Housing:	Aluminum Alloy
Finish:	Powder Coating
Color:	Black
Mounting:	Bracket Mount Ceiling Mount Suspended Mount
Lens:	Polycarbonate Optical Lens, Glass
Voltage:	Standard: 120-277V
Operating Temperature:	-20°C to + 45°C(-4°F to 113°F)
Power Factor:	>.9
CRI:	80
Surge Protector:	1kV line-line, 2kV line-earth
Dimming:	0-10V DMX
Warranty:	10-Years Warranty

## Performance Data

### Lumen Output:

1,800 to 3,600 lm

### Lumens Per Watt (typical):

100 lm/W

### CCT:

4000K (2200K, 3000K, 5000K optional)

RGB ( R:620-630nm, G:520-530mm, B:470-480mm )

RGBW ( R:620-630nm, G:520-530mm, B:470-480mm,  
W:4000K )

## Ratings & Certificates

ETL Listed

IP66




Intertek




## Dimensions

Item	Width	Length	Height
18W	4.76"	20.00"	3.11"
36W	4.76"	39.29"	3.11"




## Photometrics

For Single White





For RGB/RGBW



## Mounting

L-Bracket		
LL-BC-F56-03	LL-BC-F56-04	LL-BC-F56-05
Ceiling Mount		
LL-BC-F56-06	LL-BC-F56-07	LL-BC-F56-08
Suspended Mount		
LL-BC-F56-10	LL-BC-F56-11	

## Accessories

Visor		Anti-Glare Film
LL-BC-F56-01	LL-BC-F56-02	LL-AG-F56-02



<b>Project Name</b>	
<b>Catalog #</b>	
<b>Job Type</b>	
<b>Prepared By</b>	
<b>Notes</b>	

## Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Dimming
LL-FL56-18-40-UNV-010	18	1800	4000	120-277	0-10V
LL-FL56-36-40-UNV-010	36	3600	4000	120-277	0-10V
LL-FL56-18-40-UNV-DMX	18	1800	4000	120-277	DMX
LL-FL56-36-40-UNV-DMX	36	3600	4000	120-277	DMX
LL-FL56-18-RGB-UNV-DMX	18	NA	RGB	120-277	DMX
LL-FL56-36-RGB-UNV-DMX	36	NA	RGB	120-277	DMX
LL-FL56-18-RGBW-UNV-DMX	18	NA	RGBW	120-277	DMX
LL-FL56-36-RGBW-UNV-DMX	36	NA	RGBW	120-277	DMX

\* Please contact LITELUME for all Custom Option Requests

## Beam Angle

Part #	Degrees
F0011	12°
F00113	30°
F00114	60°
F00115	15x30°
F00116	20x60°
F00117	75°
F00118	8°
F00121	15° for RGB/RGBW
F00122	25° for RGB/RGBW
F00123	15x30° for RGB/RGBW
F00124	60° for RGB/RGBW

## Mounting Option

Part #	Description
LL-BC-F56-03	L Bracket (3.93")
LL-BC-F56-04	L Bracket (5.51")
LL-BC-F56-05	L Bracket (7.08")
LL-BC-F56-06	Ceiling Mount Bracket (2.36")
LL-BC-F56-07	Ceiling Mount Bracket (4.72")
LL-BC-F56-08	Ceiling Mount Bracket (7.08")
LL-BC-F56-10	Suspension Kit
LL-BC-F56-11	Suspension Kit



## Accessories

Part #	Description
LL-BC-F56-01	Visor for 18W
LL-BC-F56-02	Visor for 36W
LL-AG-F56-02	Anti-Glare film