





Description

The Litelume Troffer Retrofit Strip (LL-TRS) is designed to transform existing fluorescent troffers or enclosures into high performance LED luminaires. Delivering general ambient lighting in a variety of indoor settings, including schools, offices, hospitals and stores. This high efficacy kit provides long-life and uniform illumination, as well as standard 0-10v DC dimming capability.

Fixture Information

Size: 20W/30W/45W/60W/90W

Housing: Aluminum Extrusion Housing with

Easy Mounting Bracket. Magnet Construction Makes Easy Prealignment on Installation

Finish: Protective powdercoat

Color: Standard: White

Lens: High Transmission Acrylic Creates

Excellent Light Distribution and

Uniformity

Dimming: Standard 0-10V

Operating Temperature: -20°C to 50°C

Power Factor: .95 CRI: 80

Voltage: Standard: 120-277V

Warranty: 10-Year Limited Warranty

Performance Data

Lumen Output:

2,600 to 7,800 lm

Lumens Per Watt (typical):

130 lm/W

CCT: 4000K

Lifespan:

100,000 Hours

Ratings & Certificates

ETL listed





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Dimension

Item	Width	Length	Height	
2x2	1"	20.7"	0.8"	
2x4	1"	44.2"	0.8"	

Fixture Ordering Information

3							
Part #	Wattage	Lumens	Kelvin	Voltage			
LL-TRS-22-2L-20-40-D	20W	2600	4000K	120-277			
LL-TRS-22-3L-30-40-D	30W	3900	4000K	120-277			
LL-TRS-24-2L-30-40-D	30W	3900	4000K	120-277			
LL-TRS-24-3L-45-40-D	45W	5850	4000K	120-277			
LL-TRS-24-4L-60-40-D	60W	7800	4000K	120-277			
LL-TRS-44-6L-90-40-D	90W	11700	4000K	120-277			