

# 8" Commercial LED Architectural **Recessed Can Trim & Frame In Kit**





### **Description**

Size:

Trim:

Frame:

Optics:

Warranty:

The LITELUME™ 8" Commercial Led Architectural Recessed Can Trim & Frame In Kit (RCTF-8) features a self-flanged deep cone aluminum reflector with frosted lens for precision light. Junction box is mounted on the frame for easy wiring, driver access and installation. Die cast aluminum heat sink for thermal management.

### **Fixture Information**

# 40W/50W Galvanized steel Tapered Aluminum 3 step LED binning process. Self-Semi-Specular finish.

CRI: Power Factor: Dimming: Voltage: Operating Temperature: Mounting:

flanged deep cone frosted lens. 80 .95 0-10V, 10% 120-277V -22° F to 104° F Standard: C Channel. Optional: Flat bar hangers available for ceiling grid mounting (order separately).

10-Year Limited Warranty

## **Performance Data**

#### Lumen Output:

3,090 to 4,530 lm

CCT:

4000K

#### Lifespan:

Features high performance LED's with up to 100,000 running hours

#### **Ratings & Certificates**

cULus listed for damp and wet locations Complies with RoHS (Restriction on Hazardous Substances) requirement Title 24 Compliant





Page 1/3





#### Dimension

Item	Height	Width
40W/50W	7″	9.375″









#### Flat Bar Hanger 27" For Architectural Cans



LITELUME ©Lite Lume Corporation 2018

www.litelume.com info@litelume.com 833.LED.LUME Page 2/3



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

### **Fixture Ordering Information**

Part #	Wattage	Lumens	Kelvin	Voltage
LL-RCTF-8-52-40-UNV-DM	52	4530	4000K	120-277V
LL-RCTF-8-40-40-UNV-DM	40	3090	4000K	120-277V

# **Accessories Ordering Information**

Part #	Description
LL-ZZ-BARHANGER-ARCHCAN-FLAT27 "	Flat Bar Hanger 27" For Architectural Cans

\* Please contact LITELUME for all Custom Option Requests

Page 3/3