







Description

The LITELUME™ Sconce Block Mood (LL–SBM) luminaire incorporates a simple fresh small form factor design. Features a die-formed cold rolled steel housing in black, with availability to special order in satin nickel, oil rubbed bronze or custom colors with a crystal glass lens. Offering a standard 10w model in 3000k or 4000k, high power factor and low THD.

Applications: commercial, residential, hospitality and entertainment.

Fixture Information

Size: 10W

Housing: Die-formed cold rolled steel
Finish: Protective powder coat
Color: Standard: Black (BK)

Optional Special Order: Satin Nickel

(SN)

Optional Special Order: Oil Rubbed

Bronze (ORB)

Optional Special Order: Custom

(CUS)

Mounting: Standard: Wall Mount
Lens: High Transmission Glass

CRI: 80
Power Factor: .90

Voltage: Standard: 120-277V
Warranty: 10-Year Limited Warranty

Performance Data

Lumen Output:

650 lm

Lumens Per Watt (typical):

65 lm/W

CCT:

3000K 4000K

Ratings & Certificates

ETL/cETL Listed
Damp Location Listed
ADA Compliant









Dimension

Item	Width	Depth	Height
10W	5.0"	3.9"	5.0"







Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SBM-10-30-UNV-BK	10	650	3000	120-277	Black

^{*} Please contact LITELUME for all Custom Option Requests

Special Order

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SBM-10-30-UNV-SN	10	650	3000	120-277	Satin Nickel
LL-SBM-10-30-UNV-ORB	10	650	3000	120-277	Oil Rubbed Bronze
LL-SBM-10-30-UNV-CUS	10	650	3000	120-277	Custom

^{*} Please contact LITELUME for all Custom Option Requests