

LL-CNYXTE





. .

New York City Compliant LED Exit & Incandescent Emergency Steel Combo

Illumination:

Description

• Two fully adjustable 12W, glare-free lamp heads with

field installable 3rd emergency lighting head included. • Knockouts provided on sides of unit to relocate lamp

heads.

• High performance smooth metal reflector and glass lens for optimal light distribution.

• Ultra bright, energy efficient, long life Red LED exit sign illumination.

• New York Compliant 8" EXIT letters.

Electrical:

• Dual 120V/277 voltage,

• Charge rate/power "ON" LED indicator light and pushto-test switch for mandated code compliance testing.

• LVD (low voltage disconnect) prevents battery from deep discharge.

• 6V maintenance-free, rechargeable sealed lead acid battery.

• Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.

• Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting:

• Mounting hardware provided for back surface wall mount.

• Knockouts provided for conduit feed applications.

Housing:

• Durable, powder-coated 20-gauge steel construction in white or black finish.

• Injection-molded, engineering grade, high-impact, thermoplastic heads.

• Field removable steel knockout Chevron directional indicators.

LITELUME[®] ©Lite Lume Corporation 2018

www.litelume.com info@litelume.com 833.LED.LUME

Options:

• SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

• Custom: Signs available with requested "special" wording.


Warranty/Listing:

- Seven year warranty on all electronics and housing. Battery prorated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

• Certified to CEC under Title 20 Regulations.



Dimensions:





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Model	el No. of Faces		Letter Color		Housing Color		Options	
LL-CNYXTE	1	Single Face	R	Red	W B	White Black	3 NH	Standard No Lamp Head

LITELUME www.litelume.com ©Lite Lume Corporation 2018
www.litelume.com
%33.LED.LUME

Page 2/2