



Flat Panel Round 3"



LL-FPR3

Flat Panel Round 3"

The LL-FPR3 Series Flat Panel Canless Downlight delivers sleek performance and versatility for modern spaces. Available in 3" with 5 CCT field selectable color temperatures ranging from 2700K to 5000K. High Performance LED's provide a vibrant light. Easy recessed installation without a housing makes it ideal for both new construction and retrofit applications. Where a frame kit is needed, we offer a universal frame kit.



PERFORMANCE DATA

Lumen Output	400 lm
Lumens Per Watt (typical)	80 lm/W
CCT - Field Selectable	2700K 3000K 3500K 4000K 5000K
Lifespan	181,000 hrs

RATINGS & CERTIFICATES

cETLus • Energy Star • FCC • IC Rated
Wet Location • Interior / Exterior

APPLICATIONS

New Construction • Retrofit & Remodel

FIXTURE INFORMATION

Size	Housing	Finish	Trim Finish	Beam Angle	Warranty	
5W	White Aluminum	Premium Powder Coat	White	110°	10 Year	
Voltage	Dimming	Electrical		PF	THD	CRI
120V	Triac Dimming @ 120V	0.5kV Surge Protection	Type IC	.90	<20%	90

Operating Temperature: -4°F to 113°F



DIMENSIONS

	Length (in)	Width (in)	Height (in)	Weight (lbs)
	3.62	3.62	0.85	0.44
	Junction Box Size (in)			3.94 x 2.68 x 1.4

LUMEN TABLES

Measurements	Lumens				
	2700K	3000K	3500K	4000K	5000K
Lumens	469	484	489	495	495
Watts	5.85	5.77	5.74	5.89	5.91
Efficacy	80.17	83.88	85.19	84.04	83.76

COMPATIBLE DIMMERS AND CONTROLS

Lutron	Leviton
<ul style="list-style-type: none"> • TG-600PR-WH • SLV-600P-AL • DVCL-153P • S-600PR-WH • DV-600PR-WH • MSCL-OP153M • CTCL-153PDH-WH • SCL-153PH-WH • PD-6WCL • TGCL-153PH-LA • GT-600P • MACL-153M//MA-R 	<ul style="list-style-type: none"> • 6672 • 6674 • IPL06 • RNL06 • DSL06



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	CCT
LL LITELUME	FPR3 Flat Panel Round 3"	4L 400 Lumens	KFS Kelvin Field Selectable

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage	Beam
LL-FPR3-4L-KFS	5W	400	5 CCT	120	110 Degree