







Description

Color:

The LITELUME™ Sconce Half Moon (LL–SHM) features a deformed cold rolled steel housing in satin nickel or oil rubbed bronze with a high transmission acrylic shade for an elegant soft appearance.

Applications: commercial, residential, hospitality,entertainment and Hallways lighting.

Fixture Information

Size: 14W

Housing: Die-formed cold rolled steel Finish: Protective powder coat

Standard: Satin Nickel (SN)
Optional: Oil Rubbed Bronze (ORB)

Mounting: Standard: Wall Mount

Lens: High transmission acrylic

CRI: 90
Power Factor: .98
THD: <10%

Dimming: Standard: No
Voltage: Standard: 120-277V
Warranty: 10-Year Limited Warranty

Performance Data

Lumen Output:

1360 lm

Lumens Per Watt (typical):

100 lm/W

CCT:

3000K

Lifespan:

60,000 hrs

Ratings & Certificates


ETL/cETL Listed Damp Location Listed





Dimension

Item	Wide	Depth	Height
14W	16"	4"	7.9"



Page 2/3



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Ordering Guide

E	Ira	nd	Fixture Type		Lumen Package		ССТ		Voltage		Finish	
L	.L	LITELUME	SHM	Sconce Half Moon	1L	1360 Lumens	30	3000K	UNV	120-277V	SN	Satin Nickel
											ORB	Oil Rubbed Bronze

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SHM-1L-30-UNV-SN	14	1360	3000	120-277	Satin Nickel
LL-SHM-1L-30-UNV-ORB	14	1360	3000	120-277	Oil Rubbed Bronze