



LL-PSF

Pendant Series F

The LITELUME™ LED Pendant Series F (LL-PSF) features a die-formed cold rolled steel housing in satin nickel, black or oil rubbed bronze with a textured glass shade for an elegant soft appearance.



PERFORMANCE DATA

Lumen Output	800 lm
Lumens Per Watt (typical)	100 lm/W
CCT	2700k
Lifespan	30,000 hrs

RATINGS & CERTIFICATES

Energy Star • cULus Listed

APPLICATIONS

Dining • Vanity • Bathrooms • Hospitals
Schools • Restaurants • Offices • Hallways
Commercial, Residential & Hospitality

FIXTURE INFORMATION

Size	Housing	Shade	Lamp	Mounting	Color	
8W	Die-Formed Cold-Rolled Steel	Textured Glass	Omni Directional ST21 Dimmable E26 LED Bulb	Ceiling	<ul style="list-style-type: none"> Black Satin Nickel Oil Rubbed Bronze 	
Voltage	Dimming Range	Dimming Protocol	PF	THD	CRI	Warranty
120V	1%	Triac (Leading Edge)	.98	<10%	80	10 Year

Dimensions: 4.8" x 8.6" x 36.0" (OD x H x H1) Note: H1- Hanging Cable Length, Adjustable



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type		Lamps
LL LITELUME	PSF Pendant Series F		1 1 Lamp
Watts	CCT	Voltage	Color
8 8W	27 2700K	120 120V	SN Satin Nickel ORB Oil Rubbed Bronze BK Black

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-PSF-1-8-27-120-SN	8	800	2700	120
LL-PSF-1-8-27-120-BK	8	800	2700	120
LL-PSF-1-8-27-120-ORB	8	800	2700	120