



# Bulkhead Square Grid Frame Econolume Series



## LL-BSGFECO

### Bulkhead Square Grid Frame Econolume Series

The LITELUME™ Bulkhead Square Grid Frame Econolume Series (LL-BSGFECO) is designed to replace HID lighting systems up to 175W MH or HPS. The Grid appearance provides a subtle aesthetic appeal. Recommended mounting heights are 8 to 16 feet.



#### PERFORMANCE DATA

Lumen Output	1700 lm
Lumens Per Watt (typical)	74 lm/W
CCT	3000K 4000K
Lifespan	70,000 hrs

#### RATINGS & CERTIFICATES


ETL, UL Listed • Wet Location • IP65

#### APPLICATIONS

Apartments • Offices • Public Buildings  
Condominiums • Schools • Malls  
General Hospitality

#### FIXTURE INFORMATION

Size	Housing			Finish	Lens	Mounting	Color
23W	Die-Cast Aluminum			Powder Coat	Opal Polycarbonate	Wall, Ceiling, Surface	Black
Voltage	PF	THD	CRI	Dimensions (H × L × W)			Warranty
120 - 277V UNV	.90	<20%	80	3.4 × 11.8 × 11.8 in.			10 Year Limited





# Bulkhead Square Grid Frame Econolume Series

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

## ORDERING GUIDE

Brand	Fixture Type	Lumen Package	Voltage	CCT	Finish	Accessories
LL LITELUME	<b>BSGFECO</b> Bulkhead Square Grid Frame Econolume Series	<b>2L</b> 1700 Lumens	<b>UNV</b> 120-277V	<b>30</b> 3000K <b>40</b> 4000K	<b>BK</b> Black	<b>PC</b> Photocell

## FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-BSGFECO-2L-UNV-30-BK	23	1700	3000	120-277
LL-BSGFECO-2L-UNV-40-BK	23	1700	4000	120-277

## ACCESSORIES ORDERING INFORMATION

Part #	Description
PC	Photocell