



# Flat Panel Round 8"



## LL-FPR8

### Flat Panel Round 8"

The LL-FPR8 Series Flat Panel Canless Downlight delivers sleek performance and versatility for modern spaces. Available in 8" with 5 CCT field selectable color temperatures ranging from 2700K to 5000K. High Performance LED's provide a Vibrant light. Easy recessed installation without a housing makes it ideal for both new construction and retrofit applications. Where a frame kit is needed, we offer a universal frame kit.



#### PERFORMANCE DATA

Lumen Output	1400 lm
Lumens Per Watt (typical)	78 lm/W
CCT - Field Selectable	2700K 3000K 3500K 4000K 5000K
Lifespan	181,000 hrs

#### RATINGS & CERTIFICATES

cETLus • Energy Star • FCC • IC Rated  
Wet Location • Interior / Exterior

#### APPLICATIONS

New Construction • Retrofit & Remodel

#### FIXTURE INFORMATION

Size	Housing	Finish	Trim Finish	Beam Angle	Warranty	
18W	White Aluminum	Premium Powder Coat	White	110°	10 Year	
Voltage	Dimming	Electrical		PF	THD	CRI
120V	Triac Dimming @ 120V	0.5kV Surge Protection	Type IC	.90	<20%	90

Operating Temperature: -4°F to 113°F



**DIMENSIONS**

	Length (in)	Width (in)	Height (in)	Weight (lbs)
	8.82	8.82	0.93	1.10
	Junction Box Size (in)			4.73 x 2.77 x 1.34

**LUMEN TABLES**

Measurements	Lumens				
	2700K	3000K	3500K	4000K	5000K
Lumens	1440	1584	1678	1702	1664
Watts	17.49	17.11	16.71	16.86	17.46
Efficacy	82.33	92.58	100.42	100.95	95.30

**COMPATIBLE DIMMERS AND CONTROLS**

Lutron	Leviton
<ul style="list-style-type: none"> <li>TG-600PR-WH</li> <li>SLV-600P-AL</li> <li>DVCL-153P</li> <li>S-600PR-WH</li> <li>DV-600PR-WH</li> <li>MSCL-OP153M</li> <li>CTCL-153PDH-WH</li> <li>SCL-153PH-WH</li> <li>PD-6WCL</li> <li>TGCL-153PH-LA</li> <li>GT-600P</li> <li>MACL-153M//MA-R</li> </ul>	<ul style="list-style-type: none"> <li>6672</li> <li>6674</li> <li>IPL06</li> <li>RNL06</li> <li>DSL06</li> </ul>



# Flat Panel Round 8"

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

## ORDERING GUIDE

Brand	Fixture Type	Lumen Package	CCT
LL LITELUME	FPR8 Flat Panel Round 8"	14L 1400 Lumens	KFS Kelvin Field Selectable

## FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage	Beam
LL-FPR8-14L-KFS	18W	1400	5 CCT	120	110 Degree