



Floodlight 70W/100W



Description

The LITELUME™ Floodlight (LL-FL) large size is a high performance LED solution designed with versatility and a slim, low profile design. The rugged, die-cast aluminum housing with UV resistant powdercoat finish minimizes wind load requirements and features an integral, watertight LED driver compartment along with high performance aluminum heat sinks.

Applications: Parking lots, Auto dealerships, Billboard, Façade, Wall Washing, Landscape, and general outdoor lighting.

Fixture Information

Size:	40W/60W/70W/80W/100W
Housing:	Die-cast Aluminum Housing
Finish:	Protective powdercoat
Color:	Standard: Bronze Custom Options: Black (BK) White (WH) Grey (GY)
Mounting:	Slipfitter Mount Trunnion Mount
Lens:	High Performance Acrylic NEMA 7H*6V optics
Surge Protector:	Optional: 10 kVA
Power Factor:	.90
CRI:	80
Temperature:	-40°F - 113°F
Voltage:	Standard: 120-277V
Sensor:	Standard: No sensor Custom: Button Photocell (120-277V)
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

8,700 to 13,300 lm

Lumens Per Watt (typical):

124 to 133lm/W

CCT:

3000K
4000K
5000K

Beam Angle:

7H*6V

Lifespan:

Up to 100,000 running hours

Ratings & Certificates

UL Listed For Wet Location
IP65 rated
DLC Premium Listed
TAA Compliant/BAA Optional







Dimension

Item	Width	Length	Height	Weight
Floodlight (70W) w/ Slipfitter Mount	4.90"	11.06"	14.21"	8.355 lb
Floodlight (70W) w/ Trunnion Mount	4.90"	11.06"	10.97"	10.163 lb
Floodlight (100W) w/ Slipfitter Mount	4.90"	11.06"	14.21"	7.429 lb
Floodlight (100W) w/ Trunnion Mount	4.90"	11.06"	10.97"	9.237 lb

Slipfitter Mount



Trunnion Mount




Mounting Options




Slipfitter Mount- Die-cast aluminum slipfitter provides flexibility in mounting from a variety of areas.

Trunnion Mount- Die-cast aluminum trunnion is easily adapted to many surfaces and allows easy fixture aiming angles.

Photometrics 70W



100W





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Beam Angle
LL-FL-70-50-UNV-N76-BZ-SF	70	8900	5000	120-277	7H*6V
LL-FL-70-40-UNV-N76-BZ-SF	70	8900	4000	120-277	7H*6V
LL-FL-70-30-UNV-N76-BZ-SF	70	8700	3000	120-277	7H*6V
LL-FL-70-50-UNV-N76-BZ-TR	70	8900	5000	120-277	7H*6V
LL-FL-70-40-UNV-N76-BZ-TR	70	8900	4000	120-277	7H*6V
LL-FL-70-30-UNV-N76-BZ-TR	70	8700	3000	120-277	7H*6V
LL-FL-100-50-UNV-N76-BZ-SF	100	13300	5000	120-277	7H*6V
LL-FL-100-40-UNV-N76-BZ-SF	100	13300	4000	120-277	7H*6V
LL-FL-100-30-UNV-N76-BZ-SF	100	13100	3000	120-277	7H*6V
LL-FL-100-50-UNV-N76-BZ-TR	100	13300	5000	120-277	7H*6V
LL-FL-100-40-UNV-N76-BZ-TR	100	13300	4000	120-277	7H*6V
LL-FL-100-30-UNV-N76-BZ-TR	100	13100	3000	120-277	7H*6V
LL-FL-[40][60][80][100]-3CCT-UNV-N76-BZ-SF-PC	40/60/80/100	6200/9000/11600/14000	3 CCT	120-277V	7H*6V
LL-FL-[40][60][80][100]-3CCT-UNV-N76-BZ-TR-PC	40/60/80/100	6200/9000/11600/14000	3 CCT	120-277V	7H*6V

* Please contact LITELUME for all Custom Option Requests

Accessories Ordering Information

Part #	Wattage
PC	Button Photocell, 120-277V
SUB "UNV" WITH "480"	480 Volt

* Please contact LITELUME for all Custom Option Requests

Buy American Act Compliant Ordering Information

Part #	Description
BAA-FL70/100	Buy American Act Compliant for Floodlight 70W/100W

* Please contact LITELUME for all Custom Option Requests