# **SLEEK CEILING**







#### **Description**

The LITELUME™ Sleek Ceiling Series (LL–SC) luminaire incorporates a low profile design. Features a die-formed cold rolled steel housing in gold or gray with a high transmission acrylic lens for a soft appearance with excellent light distribution and uniformity.

Applications: commercial, residential, hospitality and entertainment.

## **Fixture Information**

Size:	17W		
Housing:	Die-formed cold rolled steel		
Finish:	Protective powder coat		
Color:	Standard: Grey with Gold Interior (GY) Optional: Custom colors available		
Mounting:	Standard: Ceiling Mount		
Lens:	High Transmission Acrylic		
Dimming:	0-10V dimming standard		
CRI:	*90 (3000K only)		
	80		
THD:	<10%		
Power Factor:	.95		
Voltage:	Standard: 120V-277v		
Warranty:	10-Year Limited Warranty		

Page 1/3

#### **Performance Data**

Lumen Output:

1350 lm

Lumens Per Watt (typical):

79 lm/W

CCT:

3000K 4000K

#### **Ratings & Certificates**

ETL/cETL Listed Damp Location Listed \*CEC Listed, Meets Title24 JA8 Requirements



te product



LITELUME ©Lite Lume Corporation 2018

www.litelume.com info@litelume.con 833.LED.LUME

LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to updat specifications without notice. Contact LITELUME™ for the most up-to-date data. Rev Date: 04/23/2024



### Dimension

Item	Diameter (a)	Height (b)
17W	16.5″	6.0″

LITELUME www.litelume.com ©Lite Lume Corporation 2018
www.litelume.com
%33.LED.LUME

Page 2/3



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

# **Fixture Ordering Information**

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-SC-17-40-UNV-GY	17	1350	4000	120-277	Grey with Gold Interior
*LL-SC-17-30-UNV-GY	17	1215	3000	120-277	Grey with Gold Interior

\*CEC Listed, Meets Title24 JA8 Requirements

Page 3/3