



Modern Classic Sconce



Description

The LITELUME™ Modern Classic Sconce (LL-MC) luminaire features a die-formed cold rolled steel housing in black, with availability or custom colors with a glass lens. Offering a standard 10w model in 3000k, high power factor and low THD.

Applications: commercial, residential, hospitality and entertainment.

Fixture Information

Size:	10W
Housing:	Die-formed cold rolled steel
Finish:	Protective powder coat
Color:	Standard: Black (BK) Optional Special Order: Oil Rubbed Bronze (ORB) Optional Special Order: White (WH) Optional Special Order: Gray (GY) Optional Special Order: Custom (CUS)
Mounting:	Standard: Wall Mount
Lens:	Seed Glass
CRI:	80
THD:	<10%
Power Factor:	.90
Sensor:	Standard: Button Photocell (120V)
Voltage:	Standard: 120V
Warranty:	10-Year Limited Warranty

Performance Data

Lumen Output:

600 lm

Lumens Per Watt (typical):

60 lm/W

CCT:

3000K

4000K

Ratings & Certificates

ETL/cETL Listed

Wet Location Listed

CEC Listed, Meets Title24 JA8 Requirements





Dimension

Item	Width	Depth	Height
10W	11.5"	9.5"	8.1"



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-MC-10-30-120-BK	10	600	3000K	120-277V	Black
LL-MC-10-40-120-BK	10	600	4000K	120-277V	Black

Special Orders

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-MC-10-30-120-WH	10	600	3000K	120-277V	White
LL-MC-10-30-120-GY	10	600	3000K	120-277V	Gray
LL-MC-10-30-120-ORB	10	600	3000K	120-277V	Oil Rubbed Bronze
LL-MC-10-30-120-CUS	10	600	3000K	120-277V	Custom
LL-MC-10-40-120-WH	10	600	4000K	120-277V	White
LL-MC-10-40-120-GY	10	600	4000K	120-277V	Gray
LL-MC-10-40-120-ORB	10	600	4000K	120-277V	Oil Rubbed Bronze
LL-MC-10-40-120-CUS	10	600	4000K	120-277V	Custom