



4" Recessed Integrated Module with Floating Gimbal



LL-IFG4

4" Recessed Integrated Module with Floating Gimbal

The LITELUME™ LL-IFG4 Brings precision and versatility to your lighting project. This recessed, canless gimbal module combines a clean, modern look with powerful adjustability, 355° rotation and 90° tilt for perfect aiming every time. 5 CCT Field-selectable color temperatures 2700K–5000K ensures the right light for any application. Long lasting efficiency, flexibility, and style without the need for a housing or junction box.



PERFORMANCE DATA

Lumen Output	700 lm
Lumens Per Watt (typical)	89 lm/W
CCT - Field Selectable	2700K 3000K 3500K 4000K 5000K
Lifespan	120,000 hrs

RATINGS & CERTIFICATES

Energy Star • FCC • IC Rated • cETLus Wet • Title 24 • JA8 • Interior / Exterior

APPLICATIONS

New Construction • Retrofit & Remodel

FIXTURE INFORMATION

Size	Housing	Finish	Optics	Trim	Beam Angle	Color	
8W	White Aluminum	Premium Powder Coat	PMMA Diffuser	Gimbal	120°	White	
Voltage	Dimming	Electrical	Adjustability	PF	THD	CRI	Warranty
120V	Triac Dimming @ 120V	1kV Surge Protection	355° Rotation and 90° Tilt	>.90	<20%	90	10 Year

Operating Temperature: -4°F to 113°F



4" Recessed Integrated Module with Floating Gimbal

DIMENSIONS

	Length (in)	Width (in)	Height (in)	Weight (lbs)
	4.80	4.80	1.47	0.66
	Junction Box Size (in)			4.15 x 2.66 x 1.36

LUMEN TABLES

Measurements	Lumens				
	2700K	3000K	3500K	4000K	5000K
Lumens	620	662	701	738	745
Watts	8.44	8.35	8.24	8.27	8.57
Efficacy	73.46	79.28	85.07	89.24	86.93

ELECTRICAL DATA

CCT	Input Amps
	Lumens
	120V
2700K	0.07
3000K	0.07
3500K	0.07
4000K	0.07
5000K	0.07



4" Recessed Integrated Module with Floating Gimbal

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	CCT
LL LITELUME	IFG4 4" Round Recessed Integrated Module with Floating Gimbal	7L 700 Lumens	5CCT 5 CCT Selectable

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage	Beam
LL-IFG4-7L-5CCT	8	700	5 CCT	120	120 Degree

COMPATIBLE DIMMERS AND CONTROLS

Manufacturer	Model Number		
Lutron	TG-600PR-WH	SLV-600P-AL	DVCL-153P
	S-600PR-WH	DV-600PR-WH	MSCL-OP153M
	CTCL-153PDH-WH	SCL-153PH-WH	PD-6WCL
	TGCL-153PH-LA	GT-600P	MACL-153M//MA-R
Leviton	6672	6674	IPL06
	RNL06	DSL06	-