

# **Jelly Jar Explosion Proof**





### Description

The Litelume Jelly Jar Explosion Proof (LL-JJEP) Class 1, Division 1 Luminaire is a low wattage security light specifically designed for general illumination at hazardous locations. Typical lighting applications include industrial facilities, marine vessels, mining, chemical production & processing, oil & gas refineries and high humidity, dust and temperature facilities.

## **Performance Data**

#### Lumen Output:

3,848 to 5,600 lm

#### Lumens Per Watt (typical):

133 to 140 lm/W

CCT: 4000K

#### 5000K **Distriution:**

Standard: 120 Degree Optional: 40,60 & 90 Degree

#### Lifespan:

Features Meanwell Driver & up to 100,000 running hours

#### **Ratings & Certificates**

NEMA 4X, IP66 IK10 UL1598 and UL1598A UI 844 CSA C22.2 No.137/No.250.0 Class I, Division 1, Groups C, D Class I, Division 2, Groups A, B, C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups EF,G Class III Marine and Wet Locations IFCFX ATFX





### Size: Housing:

**Fixture Information** 

Finish: Color:

Mounting:

Lens: CRI Dimming: Temperature: Voltage: Power Factor: Surge Protector: Warranty:

30W/40W

Die-cast Aluminum Housing Powder Coat Finish Over a Chromate Conversion Coating

Standard: Grey

Standard: Ceiling, Wall, or Surface Mount. Accepts NPT3/4 or M25. Optional: Pendant, Pole or Wall Mount Arm; Please see accessories for ordering instructions

**Clear Tempered Glass** 80

Standard: 0-10V

-25°C to +50°C

120-277V

>.90 6 kVA

Page 1/3

10-Year Limited Warranty


LITELUME ©Lite Lume Corporation 2018

www.litelume.com nfo@litelume.co 833.LED.LUME Rev Date: 02/22/2024



### **Dimension**

Item	Height	Diameter
30W/40W	12.26″	6.89″



LITELUME ©Lite Lume Corporation 2018

www.litelume.com info@litelume.com 833.LED.LUME Rev Date: 02/22/2024

Page 2/3



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

# **Fixture Ordering Information**

Part #	Wattage	Lumens	Kelvin	Voltage	Distribtion
LL-JJEP-30-50-UNV-GY	30	4050	5000	120-277V	120
LL-JJEP-30-40-UNV-GY	30	3848	4000	120-277	120
LL-JJEP-40-50-UNV-GY	40	5600	5000	120-277	120
LL-JJEP-40-40-UNV-GY	40	5320	4000	120-277	120

# Accessories Ordering Information

Part #	Description
PS	Pole Stanchion
PS25	25° Pole Stanchion
WMA	Wall Mount Arm
PM12	12" Pendant
PMB12	12" Bent Pendant
JB	Junction Box

\* Please contact LITELUME for all Custom Option Requests