



6" Trim Recessed Module Gimbal Downlight



LL-MODGR6

6" Trim Recessed Module Gimbal Downlight

The LITELUME™ LL-MODGR6 Trim Recessed Module Gimbal Downlight delivers sleek performance and versatility for modern spaces. Available in 6" with 5 CCT field selectable color temperatures ranging from 2700K to 5000K. Aesthetic appeal and elegant illumination. Pairs with our LED dedicated 4" can with quick connector, ideal for new construction, or use the screw-in adapter to retrofit any 6" incandescent can for a perfect energy upgrade.



PERFORMANCE DATA

Lumen Output	1000 lm
Lumens Per Watt (typical)	71 lm/W
CCT - Field Selectable	2700K 3000K 3500K 4000K 5000K
Lifespan	174,000 hrs

RATINGS & CERTIFICATES

Energy Star • FCC • IC Rated
cETLus • Damp • Title 24 • JA8

APPLICATIONS

New Construction • Retrofit & Remodel

FIXTURE INFORMATION

Size	Housing	Finish	Optics	Trim Type	Color		
14W	White Aluminum	Premium Powder Coat	Polycarbonate Diffuser	Gimbal	White		
Voltage	Dimming	Electrical	Adjustability	PF	THD	CRI	Warranty
120V	Triac Dimming @ 120V	1kV Surge Protection	Max. Tilts Angle 60° & Swivels a Full 360°	>.90	<20%	90	10 Year

Operating Temperature: -4°F to 113°F



6" Trim Recessed Module Gimbal Downlight

DIMENSIONS

	Length (in)	Width (in)	Height (in)	Weight (lbs)
	7.39	7.39	2.8	0.66

COMPATIBLE DIMMERS AND CONTROLS

Manufacturer	Model Number		
Lutron	TG-600PR-WH	SLV-600P-AL	DVCL-153P
	S-600PR-WH	DV-600PR-WH	MSCL-OP153M
	CTCL-153PDH-WH	SCL-153PH-WH	PD-6WCL
	TGCL-153PH-LA	GT-600P	MACL-153M//MA-R
Leviton	6672	6674	IPL06
	RNL06	DSL06	-



6" Trim Recessed Module Gimbal Downlight

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	CCT
LL LITELUME	MODGR6 6" Trim Recessed Module Gimbal Downlight	10L 1000 Lumens	KFS Kelvin Field Selectable

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-MODGR6-10L-KFS	14	1000	5 CCT	120