




## Puff Square



### Description

The LITELUME™ Puff Square (LL-PSQ) features a die-formed cold rolled steel housing with a high transmission polycarbonate lens for a soft appearance. Available in 2700K, 3000K, 35000K, 4000K, 5000K field selectable with high power factor and low THD.

Applications: commercial, residential, hospitality and entertainment.

### Fixture Information

Size:	14W/20W
Housing:	Die-formed cold rolled steel
Finish:	Protective powder coat
Color:	Standard: White (WH)
Mounting:	Standard: Ceiling Mount
Lens:	PC
CRI:	80
Power Factor:	.90
THD:	<10%
Dimming:	Standard: TRIAC 120V DIMMING
Voltage:	Standard: 120V
Warranty:	10-Year Limited Warranty

### Performance Data

#### Lumen Output:

1000 to 1500 lm

#### Lumens Per Watt (typical):

91 - 107 LPW

#### CCT:

2700K  
3000K  
3500K  
4000K  
5000K

#### Lifespan:

Long-life LEDs provide at least 70% of initial lumen output (L70) for 157,000 hours of operation.\*\*

#### Ratings & Certificates



ETL Listed for damp locations





## Dimension

Item	Height	Width	Length
14W	3"	12"	12"
20W	3"	14"	14"





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

## Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage
LL-PSQ-14-5CCT-120-WH	14	1000	5 CCT	120
LL-PSQ-20-5CCT-120-WH	20	1500	5 CCT	120