



Pendant Series D



LL-PSD

Pendant Series D

The LITELUME™ LED Pendant Series D (LL-PSD) features a die-formed cold rolled steel housing in satin nickel, black or oil rubbed bronze with a cracking glass shade for an elegant soft appearance.



PERFORMANCE DATA

Lumen Output	800 lm
Lumens Per Watt (typical)	100 lm/W
CCT	2700k
Lifespan	30,000 hrs

RATINGS & CERTIFICATES

Energy Star • cULus Listed

APPLICATIONS

Dining • Vanity • Bathrooms • Hospitals
 Schools • Restaurants • Offices • Hallways
 Commercial, Residential & Hospitality

FIXTURE INFORMATION

Size	Housing	Shade	Lamp	Mounting	Color	
8W	Die-Formed Cold-Rolled Steel	Cracking Glass	Omni Directional ST21 Dimmable E26 LED Bulb	Ceiling	<ul style="list-style-type: none"> • Black • Satin Nickel • Oil Rubbed Bronze 	
Voltage	Dimming Range	Dimming Protocol	PF	THD	CRI	Warranty
120V	1%	Triac (Leading Edge)	.98	<10%	80	10 Year

Dimensions: 5.9" x 11.4" x 36.0" (OD x H x H1) **Note:** H1- Hanging Cable Length, Adjustable



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type		Lamps
LL LITELUME	PSD Pendant Series D		1 1 Lamp
Watts	CCT	Voltage	Color
8 8W	27 2700K	120 120V	SN Satin Nickel ORB Oil Rubbed Bronze BK Black

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage
LL-PSD-1-8-27-120-SN	8	800	2700	120
LL-PSD-1-8-27-120-BK	8	800	2700	120
LL-PSD-1-8-27-120-ORB	8	800	2700	120