





Description

Chicago Approved All Led Exit/Stair Sign & Emergency Steel Combo

Illumination:

- Long lasting, energy efficient white LED EXIT or STAIR sign illumination .
- \bullet Two 6V 5.3W adjustable Chicago approved white LED lamp heads.

Electrical:

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and pushto-test switch for mandated code compliance testing.
- 6V sealed lead acid, maintenance-free, rechargeable battery.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 120-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

Mounting:

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

Housing:

- Durable, powder-coated 20-guage steel construction in white or black finish.
- EZ snap-out chevron directional indicators.

Options


• RC: Remote capacity of up to 10.0 watts.

Warranty/Listing:

- Seven year warranty on all electronics and housing. Battery prorated two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 40°C).
- Meets city of Chicago requirements.



Dimensions:





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Model	No	No. of Faces		Letter Color		using Color	Options		Signage / Directional Arrows		
LL-CALEDCXTEU	1 2	Single Face Universal Single/ Double Face	R G	Red Green	W B	White Black	RC	Remote Capacity	-NA -S-NA -DA -S-DA -RA ¹ -S-RA ¹ -LA ¹ -S-LA ¹ -LARA ² -S-LARA ²	Exit No Arrow Stairs No Arrow Exit Double Arrow Stair Double Arrow Exit Right Arrow Stair Right Arrow Exit Left Arrow Stair Left Arrow Exit Left/Right Arrow Stair Left/Right Arrow	

Available in single face configuration only.

Available in double face configuration only.