

Ceiling Ring Light





Description

The LITELUME™ Ceiling Ring Lite (LL–CRL) features a die-formed cold rolled steel housing in grey or oil rubbed bronze with a high transmission acrylic lite ring for an elegant soft appearance. Featuring 3 different sizes and wattages, and select wattage models available in a suspended mount. Available in 3000k or 4000k with optional EM battery backup and bi-level, high power factor and low THD.

Applications: hospitality and entertainment

Fixture Information

Size:	21W/34W/44W			
Housing:	Die-formed cold rolled steel			
Finish:	Protective powder coat			
Color:	Standard: Grey (GY) Standard: Oil Rubbed Bronze (ORB)			
Mounting:	Standard: Ceiling Mount, Suspended Mount			
Lens:	High Transmission Acrylic			
CRI:	80			
Power Factor:	.90			
Voltage:	Standard: 120-277V			
Warranty:	10-Year Limited Warranty			

Performance Data

Lumen Output:

1260 to 2330 lm

Lumens Per Watt (typical):

53 to 63 lm/W

CCT: 3000K

4000K

Ratings & Certificates

ETL/cETL Listed Damp Location Listed





LITELUME[~] ©Lite Lume Corporation 2018 www.litelume.com info@litelume.com 833.LED.LUME

om Page 1/3 om Rev Date: 10/21/2023

LITELUME™ seeks to deliver the most advanced and efficient LED technology. Due to technology progression, specifications may change. We reserve the right to update product specifications without notice. Contact LITELUME™ for the most up-to-date data.

Dimension

ltem	Diameter (a)	Height (b)	Height2 (c)
21W	11.8″	2.8″	-
34W	15.8″	2.8″	-
44W	19.7″	2.8″	-
44W (Suspended)	19.7″	2.8″	6"



Page 2/3



Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-CRL-21-40-UNV-ORB	21	1260	4000	120-277	Oil Rubbed Bronze
LL-CRL-21-40-UNV-GY	21	1260	4000	120-277	Grey
LL-CRL-21-30-UNV-ORB	21	1260	3000	120-277	Oil Rubbed Bronze
LL-CRL-21-30-UNV-GY	21	1260	3000	120-277	Grey
LL-CRL-34-40-UNV-ORB	34	1980	4000	120-277	Oil Rubbed Bronze
LL-CRL-34-40-UNV-GY	34	1980	4000	120-277	Grey
LL-CRL-34-30-UNV-ORB	34	1980	3000	120-277	Oil Rubbed Bronze
LL-CRL-34-30-UNV-GY	34	1980	3000	120-277	Grey
LL-CRL-44-40-UNV-ORB	44	2330	4000	120-277	Oil Rubbed Bronze
LL-CRL-44-40-UNV-GY	44	2330	4000	120-277	Grey
LL-CRL-44-30-UNV-ORB	44	2330	3000	120-277	Oil Rubbed Bronze
LL-CRL-44-30-UNV-GY	44	2330	3000	120-277	Grey

Suspended Mount

Part #	Wattage	Lumens	Kelvin	Voltage	Color
LL-CRL-SM-44-40-UNV-ORB	44	2330	4000	120-277	Oil Rubbed Bronze
LL-CRL-SM-44-40-UNV-GY	44	2330	4000	120-277	Grey
LL-CRL-SM-44-30-UNV-ORB	44	2330	3000	120-277	Oil Rubbed Bronze
LL-CRL-SM-44-30-UNV-GY	44	2330	3000	120-277	Grey