



Flat Panel Round 6"



LL-FPR6

Flat Panel Round 6"

The LL-FPR6 Series Flat Panel Canless Downlight delivers sleek performance and versatility for modern spaces. Available in 6" with 5 CCT field selectable color temperatures ranging from 2700K to 5000K. High Performance LED's provide a Vibrant light. Easy recessed installation without a housing makes it ideal for both new construction and retrofit applications. Where a frame kit is needed, we offer a universal frame kit.



PERFORMANCE DATA

Lumen Output	1000 lm
Lumens Per Watt (typical)	67 lm/W
CCT - Field Selectable	2700K 3000K 3500K 4000K 5000K
Lifespan	181,000 hrs

RATINGS & CERTIFICATES

cETLus • Energy Star • FCC • IC Rated
Wet Location • Interior / Exterior

APPLICATIONS

New Construction • Retrofit & Remodel

FIXTURE INFORMATION

Size	Housing	Finish	Trim Finish	Beam Angle	Warranty	
15W	White Aluminum	Premium Powder Coat	White <i>* Black or Brushed Nickel Finish Trim Rings Available</i>	110°	10 Year	
Voltage	Dimming	Electrical		PF	THD	CRI
120V	Triac Dimming @ 120V	0.5kV Surge Protection	Type IC	.90	<20%	90

Operating Temperature: -4°F to 113°F



DIMENSIONS

	Length (in)	Width (in)	Height (in)	Weight (lbs)
	6.73	6.73	0.79	0.88
	Junction Box Size (in)			4.73 x 2.77 x 1.34

LUMEN TABLES

Measurements	Lumens				
	2700K	3000K	3500K	4000K	5000K
Lumens	1180	1267	1316	1330	1278
Watts	14.32	14.03	13.77	14.06	14.53
Efficacy	82.40	90.31	95.57	94.59	87.96

COMPATIBLE DIMMERS AND CONTROLS

Lutron	Leviton
<ul style="list-style-type: none"> TG-600PR-WH SLV-600P-AL DVCL-153P S-600PR-WH DV-600PR-WH MSCL-OP153M CTCL-153PDH-WH SCL-153PH-WH PD-6WCL TGCL-153PH-LA GT-600P MACL-153M//MA-R 	<ul style="list-style-type: none"> 6672 6674 IPL06 RNL06 DSL06



PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Brand	Fixture Type	Lumen Package	CCT	Accessories
LL LITELUME	FPR6 Flat Panel Round 6"	10L 1000 Lumens	KFS Kelvin Field Selectable	TR-BK Trim Ring Black Finish TR-BN Trim Ring Brushed Nickel Finish

FIXTURE ORDERING INFORMATION

Part #	Watts	Lumens	Kelvin	Voltage	Beam
LL-FPR6-10L-KFS	15W	1000	5 CCT	120	110 Degree

ACCESSORIES ORDERING INFORMATION

Part #	Description
LL-FPR6-TR-BK	Trim Ring Black Finish LL-FPR6
LL-FPR6-TR-BN	Trim Ring Brushed Nickel Finish LL-FPR6