



High Bay Round UFO Explosion Proof



Description

The Litelume High Bay Round UFO Explosion Proof (LL-HBRUEP) Class 1, Division 1 Luminaire is available with a clear tempered glass lens. Typical lighting applications include industrial facilities, marine vessels, mining, chemical production & processing, oil & gas refineries and high humidity, dust and temperature facilities.

Fixture Information

Size:	20W/60W/100W/150W/200W/280W
Housing:	Die-cast Aluminum Housing
Finish:	Powder Coat Finish Over a Chromate Conversion Coating
Color:	Standard: Grey
Mounting:	Standard: Ceiling, Wall, or Surface Mount U Bracket. Accepts NPT3/4 or M25. Optional: Hook, Pendant; Please see accessories for ordering instructions.
Lens:	Clear Tempered Glass
CRI:	80
Dimming:	Standard: 0-10V
Temperature:	-40°C to +60°C
Voltage:	Standard: 120-277V Optional: 277-480V
Power Factor:	>.90
Surge Protector:	6 kVA
Warranty:	Standard Luminaire: 10-Year Limited Warranty With 8w emergency battery backup: 5-Year Limited Warranty

Performance Data

Lumen Output:

2,660 to 39,200 lm

Lumens Per Watt (typical):

133 to 140 lm/W

CCT:

4000K

5000K

Distribution:

Standard: 120 Degree

Optional: 40,60 & 90 Degree

Lifespan:

Features Meanwell Driver & with up to 100,000 running hours

Ratings & Certificates

Marking Atex

II2 G Ex db op is IIB T5/T6 Gb

II2 D Ex op is tb IIIC T80/90C Db IP66

Marking IECEX

Ex db op is IIB T5/T6 Gb

Ex op is tb IIIC T80/90C Db IP66

Marking UL844 (North American)

Class I, Division 1, Groups C, D

Class I, Division 2, Groups A, B, C, D

Class II, Division 1, Groups E, F, G

Class II, Division 2, Groups F, G

Class III

Marine Marking

UL 1598, UL1598A

ABS

Other Rating

IP 66

IK 10



QuickShip Ordering Information

Part #
LL-HBRUEP-100-50-UNV-GY
LL-HBRUEP-150-50-UNV-GY



Dimension

Item	Height	Diameter
20W-60W	8.42"	14.08"
100W-150W	13.41"	15.98"
200W-280W	10.00"	17.44"

20W-60W	
100W-150W	
200W-280W	

Photometrics


LL-HBRUEP-150-50-UNV-GY 40°	LL-HBRUEP-150-50-UNV-GY 60°	LL-HBRUEP-150-50-UNV-GY 90°	LL-HBRUEP-150-50-UNV-GY 120°																																																																								
150W/40D <table><thead><tr><th></th><th>Center Beam fc</th><th>Beam Width h</th></tr></thead><tbody><tr><td>4ft</td><td>1324fc</td><td>11ft</td></tr><tr><td>8ft</td><td>330fc</td><td>22ft</td></tr><tr><td>12ft</td><td>147fc</td><td>34ft</td></tr><tr><td>16ft</td><td>81fc</td><td>43ft</td></tr><tr><td>20ft</td><td>49fc</td><td>56ft</td></tr></tbody></table> ■ Vert.Spread:40 ° ■ Horiz.Spread:40 °		Center Beam fc	Beam Width h	4ft	1324fc	11ft	8ft	330fc	22ft	12ft	147fc	34ft	16ft	81fc	43ft	20ft	49fc	56ft	150W/60D <table><thead><tr><th></th><th>Center Beam fc</th><th>Beam Width h</th></tr></thead><tbody><tr><td>4ft</td><td>981fc</td><td>11ft</td></tr><tr><td>8ft</td><td>245fc</td><td>22ft</td></tr><tr><td>12ft</td><td>109fc</td><td>34ft</td></tr><tr><td>16ft</td><td>60fc</td><td>45ft</td></tr><tr><td>20ft</td><td>39fc</td><td>56ft</td></tr></tbody></table> ■ Vert.Spread:60 ° ■ Horiz.Spread:60 °		Center Beam fc	Beam Width h	4ft	981fc	11ft	8ft	245fc	22ft	12ft	109fc	34ft	16ft	60fc	45ft	20ft	39fc	56ft	150W/90D <table><thead><tr><th></th><th>Center Beam fc</th><th>Beam Width h</th></tr></thead><tbody><tr><td>4ft</td><td>701fc</td><td>11ft</td></tr><tr><td>8ft</td><td>175fc</td><td>22ft</td></tr><tr><td>12ft</td><td>78fc</td><td>34ft</td></tr><tr><td>16ft</td><td>43fc</td><td>45ft</td></tr><tr><td>20ft</td><td>28fc</td><td>56ft</td></tr></tbody></table> ■ Vert.Spread:90 ° ■ Horiz.Spread:90 °		Center Beam fc	Beam Width h	4ft	701fc	11ft	8ft	175fc	22ft	12ft	78fc	34ft	16ft	43fc	45ft	20ft	28fc	56ft	150W/120D <table><thead><tr><th></th><th>Center Beam fc</th><th>Beam Width</th></tr></thead><tbody><tr><td>4ft</td><td>508fc</td><td>11ft</td></tr><tr><td>8ft</td><td>125fc</td><td>22ft</td></tr><tr><td>12ft</td><td>56fc</td><td>34ft</td></tr><tr><td>16ft</td><td>31fc</td><td>45ft</td></tr><tr><td>20ft</td><td>20fc</td><td>56ft</td></tr></tbody></table> ■ Vert.Spread:120 ° ■ Horiz.Spread:120 °		Center Beam fc	Beam Width	4ft	508fc	11ft	8ft	125fc	22ft	12ft	56fc	34ft	16ft	31fc	45ft	20ft	20fc	56ft
	Center Beam fc	Beam Width h																																																																									
4ft	1324fc	11ft																																																																									
8ft	330fc	22ft																																																																									
12ft	147fc	34ft																																																																									
16ft	81fc	43ft																																																																									
20ft	49fc	56ft																																																																									
	Center Beam fc	Beam Width h																																																																									
4ft	981fc	11ft																																																																									
8ft	245fc	22ft																																																																									
12ft	109fc	34ft																																																																									
16ft	60fc	45ft																																																																									
20ft	39fc	56ft																																																																									
	Center Beam fc	Beam Width h																																																																									
4ft	701fc	11ft																																																																									
8ft	175fc	22ft																																																																									
12ft	78fc	34ft																																																																									
16ft	43fc	45ft																																																																									
20ft	28fc	56ft																																																																									
	Center Beam fc	Beam Width																																																																									
4ft	508fc	11ft																																																																									
8ft	125fc	22ft																																																																									
12ft	56fc	34ft																																																																									
16ft	31fc	45ft																																																																									
20ft	20fc	56ft																																																																									



Mounting

Shown with PM12 (12" PENDANT) + JB (JUNCTION BOX)	PMB12 - 12" BENT PENDANT	HM - HOOK MOUNT
		
JB - JUNCTION BOX	PM12 - 12" PENDANT	
		

Cable Entries





Project Name	
Catalog #	
Job Type	
Prepared By	
Notes	

Fixture Ordering Information

Part #	Wattage	Lumens	Kelvin	Voltage	Distribution
LL-HBRUEP-20-50-UNV-GY	20	2800	5000	120-277V	120
LL-HBRUEP-20-40-UNV-GY	20	2660	4000	120-277V	120
LL-HBRUEP-60-50-UNV-GY	60	8400	5000	120-277V	120
LL-HBRUEP-60-40-UNV-GY	60	7980	4000	120-277V	120
LL-HBRUEP-100-50-UNV-GY	100	14000	5000	120-277V	120
LL-HBRUEP-100-40-UNV-GY	100	13300	4000	120-277V	120
LL-HBRUEP-150-50-UNV-GY	150	21000	5000	120-277V	120
LL-HBRUEP-150-40-UNV-GY	150	19950	4000	120-277V	120
LL-HBRUEP-200-50-UNV-GY	200	28000	5000	120-277V	120
LL-HBRUEP-200-40-UNV-GY	200	26600	4000	120-277V	120
LL-HBRUEP-280-50-UNV-GY	280	39200	5000	120-277V	120
LL-HBRUEP-280-40-UNV-GY	280	37240	4000	120-277V	120

* Please contact LITELUME for all Custom Option Requests

QuickShip Ordering Information

Part #
LL-HBRUEP-100-50-UNV-GY
LL-HBRUEP-150-50-UNV-GY

Distribution Type Ordering Information (Standard:120°)

Part #	Description
40D	40°
60D	60°
90D	90°

* Please contact LITELUME for all Custom Option Requests

Accessories Ordering Information

Part #	Description
SUB "UNV" WITH "HV"	277-480 Volt
EM8X	Emergency Battery Back Up 8W Exclusive **120-277V ONLY** / **100W - 280W ONLY**
HM	Hook Mount
PM12	12" Pendant *20W/60W Only*
PMB12	12" Bent Pendant *20W/60W Only*
JB	Junction Box
SC	Safety Chain

* Please contact LITELUME for all Custom Option Requests