



Steel Housing LED Emergency Unit



LL-LESDXR627

Steel Housing LED Emergency Unit

Long lasting, efficient, ultra bright white LED lamp heads. 1.5 watt (12 LEDs x 0.125 watt) per head. High performance chrome-plated metallized reflector and plastic lens for optimal light distribution. Adjustable LED lamp heads provide optimal center-to-center spacing.



PRODUCT INFORMATION

Illumination	Electrical
<ul style="list-style-type: none"> • 1.5 watt (12 LEDs x 0.125 watt) per head. • Long lasting, efficient, ultra bright white LED lamp heads. • High performance chrome-plated metallized reflector and plastic lens for optimal light distribution. • Adjustable LED lamp heads provide optimal center-to-center spacing. 	<ul style="list-style-type: none"> • Dual 120V/277V. • Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. • LVD (low voltage disconnect) prevents battery from deep discharge. • 6V sealed lead acid, maintenance-free, rechargeable battery. • Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination. • Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours. • Remote capacity of 20W standard. • Runs up to 8 hours without remote heads.
Housing	<h4>Dimensions</h4>
<ul style="list-style-type: none"> • Durable 20-gauge steel construction. • White or black finish. 	
Mounting	<h4>Warranty</h4>
<ul style="list-style-type: none"> • Knockouts on the back for wall mount. • Side and top knockouts for conduit feed applications. 	<ul style="list-style-type: none"> • Five year warranty on all electronics and housing. Battery prorated for two years. • UL Listed for damp locations (20°C – 50°C) standard. • Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.



Steel Housing LED Emergency Unit

PROJECT NAME	
CATALOG #	
JOB TYPE	
PREPARED BY	
NOTES	

ORDERING GUIDE

Model	Voltage	Watts	Housing Color
LL-LESDXR627	6 6V	27 27W	WH White BK Black

ELECTRICAL INFORMATION

Model	Input Watts (W)		Input Amps (A)	
LL-LEDXR	120V	277V	120V	277V
	11.0	11.0	0.11A	0.04A

REMOTE LAMP COMPATIBILITY

Model	Battery	Remote Capacity	Compatible Remote Head Family											
			LL-MRHLED	LL-RHLED	LL-RH16LED	LL-RH16		LL-RH		LL-RHR		LL-SRH		LL-SRHLED
				MV		6V	12V	6V	12V	6V	12V	6V	12V	
LL-LESDXR627	6V	20W		X	X	X		X		X		X		X